



- A Insulating grip, see chart for color
- B Terminal male 99,9% zinc
- C Nominal current inmoulded
- D Test points
- E Nominal voltage

RATING [A]	COLOR	VOLTAGE [V]
3	Violet	32
4	Pink	32
5	Tan	32
7,5	Brown	32
10	Red	32
15	Blue	32
20	Yellow	32
25	Natural	32
30	Green	32

FUSING TIME DIN 72581-3 ISO 8820-3		
LOAD [%]	MIN [s]	MAX [s]
110	360.000	-
135	0,75	600
160	0,25	50
200	0,15	5
350	0,04	0,5
600	0,02	0,1

UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE IN MILLIMETERS
 SURFACE FINISH:
 TOLERANCES: 0,2
 LINEAR:
 ANGULAR:

FINISH:

DEBUR AND
 BREAK SHARP
 EDGES

DO NOT SCALE DRAWING

REVISION

SERTRONIC

NAME	SIGNATURE	DATE		
DRAWN	B.D.	12.2014		
CHK'D				
APPV'D				
MFG				
Q.A			MATERIAL:	
			WEIGHT: 0,7 g	

TITLE:		MINI fuses family Sermovil Automoción SL	
DWG NO.			
		A4	
SCALE: 5:1		SHEET 1 OF 1	