



Table 1

Item Code	Part Description	Clamping Range $\phi d-D$	Shipping Dia. $\phi D +2$
AM25	WD9 25-40 C7 W2	25-40	40

NOTES

- 1- Recommended Tightening Torque : 3,0-3,5 Nm
- 2- Maximum Test Torque : 4,0 Nm
- 3- Recommended Tightening Speed : 300-350 rpm
- 4- Corrosion Resistance (ISO9927) : min. 72 hours

Table 2

Part	Qty.	Part Name	Material
			W2
1	1	Housing	1.4016 DIN EN 10088-2
2	1	Screw	Mild Steel*
3	1	Band	1.4016 DIN EN 10088-2

Sermovil Automoción S.L.

* Zinc Plated

INDEX		DESCRIPTION			DATE	DRAWN	ONAY CHECKED
-		New edition			07.10.2025		
CALCULATED	WEIGHT ACTUAL	VOLUME	MATERIAL	HARDNESS	GENERAL TOLERANCE	FORM AND POS.TOL.	DEVIATION FOR ANGLE
-	-	- CM ³	See Part List		DIN ISO 2768- m	DIN ISO 2768- K	-
DRAWN		NAME		DATE	PART NAME		PROJ.METH.
APPROVED				07.10.2025	Worm Drive Hose Clamp 9mm		DIN 6
SURFACE QUALITY		PART NO		SCALE	INDEX	SHEET 1/1	
				-	02	DIN A3	
ENQUIRY NO: -		DRAWING NO :		PROJECT NO.: -			
PATENT NO: --		DRAWING NAME :		MODEL:			