

Sermovil Automoci3n, S.L. Sertronic group

C/ Santiago Rusinyol, 14 NAVE A9 Pol. Ind. Can Humet de Dalt

08130 – Polinya BARCELONA - SPAIN

www.sertronic.es Tel. +34 902 111 335 Fax. +34 902 111 336 sermovil@sertronic.es

Doc. FH11 2011

Technical Characteristics



Características del producto:
Product characteristics

CONECTORES GAMA SEAL 1,5mm

Aplicaciones: Maquinaria industrial, automoci3n y agricultura

Terminales: CuZn / CuSn. Estañados. Mximo 14A. 0.35-0.50mm/0.75-1.50mm/1.5-2.5mm

Seals: goma silicona. Amarilla. 1.2-1.6 mm diametro.

Conectores:

Poliamida 6.6

Negro

Goma de silicona

1 via a 6 vias

CONNECTORS RANGE SEAL 1,5mm

Application: industrial machinery, automotive and agriculture.

Contact terminals: Cu/CuSn. Tin plated. Max. 14A 0.35-0.50mm/0.75-1.50mm/1.5-2.5mm

Seals: Silicon rubber. Yellow. 1.2-1.6mm diameter.

Connectors:

PA6.6

Black

Silicon Rubber

1 position to 6 positions

Segn/according/compliant:

DIN40050-9

IEC60529

RoHS

ELV

Sermovil Automoci3n, S.L.